

BLANK PAGE



IS: 11596 - 1986

Indian Standard SPECIFICATION FOR GRADING OF UNCUT INDIAN BIMLI

UDC 677'142: 006'73



@ Copyright 1987

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

IS: 11596 - 1986

of

Laboratories

Council,

Indian Standard SPECIFICATION FOR GRADING OF UNCUT INDIAN BIMLI

Jute and Jute Products Sectional Committee. TDC 3

Chairman

Representing

SHRI B. R. BASU

Jute Commissioner, Calcutta

Members

SHRI U. S. BAID SHRI S. CHATTERJEE (Alternate)

SHRI A. T. BASAK

SHRI S. K. BHATTACHARYA SHRI A. N. SANYAL (Alternate)

SHRI RATICHAND BOTHRA CHAIRMAN

SHRI G. M. BHANDARI (Alternate I) SHRI S. N. MUNDRA (Alternate II)

SHRI K. K. CHATTERIEE

Pesticides Association of India, New Delhi

Inspection Wing, Directorate General Supplies & Disposals, New Delhi

Jute Corporation of India Ltd, Calcutta

Calcutta Baled Jute Association, Calcutta Indian Jute Mills' Association Calcutta

Export Inspection Council of India. Calcutta

Office of the Jute Commissioner, Calcutta

Manufactures' Development

Eskaps (India) Private Ltd, Calcutta

National Jute Manufactures' Corporation Ltd, Calcutta

(ICAR), Calcutta

Ministry of Defence (DGI)

Ministry of Defence (R & D)

SHRI A. C. BISWAS (Alternate) DR C. R. DEBNATH Jute Technological Research

SHRI O. P. DHAMIJA

SHRI G MITRA (Alternate) SHRI D. K. DUTT

SHRI SEKHAR GUHA SHRI KAJAL SEN (Alternate)

SHRI D. GUPTA

SHRI G. SIVARAMAN (Alternate) Cement Manufacturers' Association, Bombay

SHRI P. J. JAGUS LT-COL P. N. MALHOTRA

SHRI A. N. MUSHRAN (Alternate) SHRI A. C. MATHUR

SHRI M. L. PAL (Alternate)

SHRIS, N. MUNDRA

Calcutta Jute Fabrics Shippers' Association, Calcutta

SHRI L. SWAMINATHAN (Alternate)

(Continued on page 2)

@ Copyright 1987

Jute

Calcutta

INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS : 11596 - 1986

(Continued from page 1)

Members

Representing

Dr V. PACHAIYAPAN SHRI S. K. PATANKAR Dr S. R. RANGANATHAN Fertilizer Association of India, New Delhi Rashtriya Chemicals & Fertilizers Ltd, Bombay Indian Jute Industries' Research Association, Calcutta

DR U. MUKHOPADHYAY (Alternate)

New Central Jute Mills Co Ltd, Calcutta SHRI T. K. ROY CHOWDHURY Indian Institute of Packaging, Bombay SHRI AMITAVA SANYAL

SHRI K. B. GUPTA (Alternate)

Food Corporation of India, New Delhi SHRI J. N. SARID

SHRI JASBIR SINGH (Alternate)

Ministry of Agricu ture SHRI A. N. SINGH SHRI R. I. MIDHA.

Director (Tex)

Director General, ISI (Ex-officio Member)

Secretary

SHRI D. R. KOHLI Joint Director (Tex), ISI

Raw Jute and Allied Fibres Subcommittee, TDC 3:1

Convener

SHRI S. K. BHATTACHARYA

Jute Corporation of India Ltd, Calcutta

Members

SHRI A. N. SANYAL (Alternate to

Shri S. K. Bhattacharya)

Jute Growers, West Bengal SHRI ABDUL RASHID

Agricultural Marketing Adviser to the Govern-AGRICULTURAL MARKETING ment of India, Faridabad ADVISER

SHRI A. S. YAWALKAR (Alternate)

Jute Growers, Assam SHRI AZAD ALI

New Central Jute Mills Co Ltd, Calcutta SHRI J. L. BAGRA

SHRI M. G. MOHTA (Alternate) Indian Jute Mills Association, Calcutta SHRI G. M. BHANDARI

Jute Brokers' Association, Calcutta SHRI A. C. BHURA Jute Growers, West Bengal SHRI NIL KAMAL BISWAS

East India Jute & Hessian Exchange Ltd. SHRI R. C. BOTHRA

Calcutta A. M. Mair & Co, Calcutta SHRI SHANTICHAND BOTHRA

Jute Agricultural Research Institute, Barrack-Dr N. K. CHAKRABARTI

DR P. C. MITRA (Alternate) DR K. CHAKRAVARTY

Ministry of Agriculture & Co-operation SHRI N. C. HALDER (Alternate)

Indian Jute Mills Association, Calcutta SHRI H. C. CHANDAK

SHRI NRIPENDRA NATH CHOUDHURY Jute Growers, West Bengal Office of the Jute Commissioner, Calcutta SHRI D. R. DAS

(Continued on page 9)

IS: 11596 - 1986

Indian Standard SPECIFICATION FOR GRADING OF UNCUT INDIAN BIMLI

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 30 January 1986, after the draft finalized by the Jute and Jute Products Sectional Committee had been approved by the Textile Division Council.
- 0.2 Grading of white, tossa and daisee uncut Indian jute has been covered in IS: 271-1975* which now forms the established basis of grading of raw jute.
- 0.3 Grading of uncut Indian mesta has been covered in IS: 9846-1981†. This standard covers grading of Bimli fibre grown specially in Andhra Pradesh. In this standard, four grades have been prescribed for Bimli. A scoring scheme has been included to grade the fibres on the basis of strength, defects, root content, colour, fineness and heaviness or lightness.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960‡. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers grading of Bimli fibres from which roots have not been cut.

2. TERMINOLOGY

- 2.0 For the purpose of this standard, the following definitions shall apply.
- 2.1 Bimli Bimli fibres are exclusively grown in Andhra Pradesh and are generally associated with underground roots since the plants are

†Grading of uncut Indian mesta.

^{*}Grading of white, tossa and daisee uncut Indian jute (second revision).

Rules for rounding off numerical values (revised).

uprooted during harvesting. It is obtained from the bark of *Hibiscus sabdarifa*, a substitute for jute. It is generally inferior and coarser than jute. Chemically, the fibre is different from jute in its low lignin content.

- **2.2 Parcel** Cor signment containing a certain number of bales, bundles or drums.
- 2.3 Strength The ability of the fibres to resist strain or rupture induced by external forces.
- 2.3.1 The strength aspect of the fibres is classified depending upon their tenacity. The terms used for the purpoes of grading are Good', 'Fair', 'Average' and 'Weak mixed'.
 - Note 1 Tenacity is the breaking load of a material under test divided by the linear density of the unstrained material, expressed as grams per tex.
 - NOTE 2 Linear density is the mass per unit length; the quotient obtained by dividing the mass of the fibre or yarn by its length. When the mass is expressed in grams and the length in kilometres, the resulting value, that is, the quotient, is expressed as tex.
- 2.4 Colour The property of fibre which distinguishes its appearance as creamy, white, grey, etc.
- 2.4.1 The colour description of fibres in relation to the terms used for the purpose of grading is given below:

Good Creamy to whitish

Average Greyish to dark

- 2.5 Fineness A measure of diameter (width) or mass per unit length, or both, of the fibre filament. The finer the fibre, the better is its spinning quality.
- 2.5.1 The fineness aspect of the fibre is classified depending upon its tex value (see Note 2 under 2.3.1).
- 2.6 Reed The fibre system from the individual Bimli plant.
- 2.7 Reed Length The length of the reed from bottom to tip excluding the underground root portions.
- 2.8 Effective Reed Length The length of the reed after the root and hard banky croppy ends have been removed.
- 2.9 Root The hard barky region at the lower end of the reed which requires additional softening treatment normally called 'cuttings'. This includes the underground root portion.

- 2.10 Centre Root (Buckchhal) The hard barky region in the middle part of the reed which requires additional softening treatment.
- 2.11 Dazed Fibre Fibre which is weak in strength and full in appearance, due to usually being stored in moist condition.
- 2.12 Over-Retted Fibre Fibre which has lost its strength and brightness due to prolonged retting.
- 2.13 Runners Hard barky fibre running from the lower end to the middle region, more or less continuously.
- 2.14 Knots Stiff barky spots in the body of the reed which break the continuity of the fibres when opened.
- 2.15 Mossy Fibre A type of vegetation which sometimes gets attached to the Bimli plant.
- 2.15.1 Its portions may remain on the fibre even after retting and washing. It can be separated by hand.
- 2.16 Sticks, Entangled Sticks and Loose Sticks Sticks are remnants of woody part of Bimli plant over which fibre sheath is formed. Entangled sticks are broken sticks which are linked with fibre mass and are not easily removable. Loose sticks are broken sticks easily removable by shaking.
- 2.17 Croppy Fibre Fibre with top ends rough and hard (but not barky) caused by careless retting.
- 2.18 Weak Croppy Fibre Fibre which has become unusually weak over a length of about 30 cm at the top end.
- 2.19 Entangled Croppy End Fibre Fibre with unusually entangled croppy end.
- 2.20 Gummy Fibre Fibres held together by undissolved pectinous matter.
- 2.21 Leaf and Loose Leaf Leaf is the dark grey leafy or paper like substance (remnant of the skin of the plant) appearing on the strand. Loose leaves are those that lie loosely on the fibre and are easily removable.
- 2.22 Specks Soft barky spots in the body where fibres can be separated with some effort without breaking their continuity, though they may remain as weak spots.
- 2.23 Natural Dust The dust which might get associated with the fibre during the process of its production.

- 2.24 Habi Jabi Tangled and ravelled Bimli of any description free of sticks.
- 2.25 Feswa Pickings of the fibre left over in the sticks of the plant after extraction of the major fibre in the process of stripping after retting.

2.26 Defects

- 2.26.1 Major Entangled croppy end fibre, centre root, dazed and over-retted fibres, runners, knots and entangled sticks.
- 2.26.2 Minor Croppy fibre, weak croppy fibre, gummy fibre, loose sticks, specks, leaves and mossy fibre.

3. UNIT OF GUARANTEE

3.1 The unit of guarantee shall be a bale, bundle or drum made of morahs or 'heads'. For purposes of appraisement, each such bale, bundle or drum shall be treated as a separate unit and shall, in itself, fulfil the guarantee of the grade.

4. GRADING

- 4.1 The Bimli fibre (from which roots have not been cut) shall be classified into 4 grades as given in Table 1.
- 4.2 The 'hand and eye' method may be used for assessing these qualities as is presently in vogue in trade but in case of any dispute, the corresponding test method applicable for jute, mesta and Bimli as mentioned in the table may also be followed for correct assessment on scientific basis.

Note — According to the trade practice for comparing strength, the tufts of fibres of approximately equal size held equal distance apart, are broken longitudinally without jerk. Good lustre indicates good fibre strength. Root content in terms of percentage by mass is judged by observing the extent of roots along the length. Light or heavy bodiedness of the fibre is assessed by feeling the lightness or heaviness of a bunch of fibre reeds (by raising and lowering) when held within a grip.

4.3 Relative weightage to each of the quality characteristics is attributed by a system of scoring for various grades by 'hand and eye' method for routine grading. The marks allocated are on the basis of the objective assessment of the different quality characteristics and as such shall be used for the purpose of grading on the basis as given in Table 1.

5. PACKING

- 5.1 The Bimli fibre should be so packed that morahs in any bale, bundle or drum are of only one grade.
- 5.2 Each bale, bundle or drum should have a grade tag indicating the year of harvest, grade and trademark.

TABLE 1 REQUIREMENTS OF FIBRE CHARACTERISTICS AND SCORING SCHEME FOR DIFFERENT GRADES OF UNCUT INDIAN BIMLI

(Clauses 4.1 and 4.3)

GRADE	Strength	DEFECTS	MAXIMUM ROOT CONTENT, PER- CENT BY MASS (WEIGHT)	Colour	FINENESS	HEAVINESS/ LIGHTNESS	TOTAL SCORE
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
B-1	Good	Free from major defects and croppy fibre and reasonably free from leaves and specks	10	Good	Fine, well segregate fibre reed		
	(25)	(30)	(30)	(6)	(3)	(6)	100
B-2	Fair	Substantially free from major defects except some knots and entangled sticks but free from weak croppy ends	(18)	Average	Coarse	Average	
	(18)	(24)	(22)	(2)	(1)	(3)	70
B-3	Average	Free from centre roots and reasonably free from over retted fibres and runners			· 		
	(10)	(15)	(15)				40
В-4		All other Bimli not conforming to any of the above grades but of commercial value. It may contain Habi Jabi but not Feswa (10)		-	_		
					·	(Con	ntinued)

TABLE 1 REQUIREMENTS OF FIBRE CHARACTERISTICS AND SCORING SCHEME FOR DIFFERENT GRADES OF UNCUT INDIAN BIMLI — Contd

Note 1 — The minimum reed length should be 150 cm or the effective reed length should not be less than 100 cm except for grade B-4. The root content includes hard barky croppy ends. For determination of strength, defects, root content, fineness, heaviness or lightness (bulk density) relevant part of IS: 7032* should be referred.

Note 2 — The fibre should be in dry storable condition,

Note 3 — The fibre should be free from mud and other foreign materials.

Note 4 — Natural dust may be allowed in Grade R-2, B-3 and B-4 with proportionate discount,

Note 5 — A parcel of Bimli which would not score full marks for a particular grade shall still be considered for that grade with suitable discount to be settled between the buyer and the seller provided its score is not less by 50 (or more) percent of the difference between the maximum scores for that and the next lower grade. When the score is less by 50 (or more) percent of the difference, the buyer will have the option to reject or settle with a suitable discount.

Note 6 — Scores in the table may be taken as guidance for determining the discount,

*Physical methods of test for white, tossa and daisee uncut Indian jute:

Part 1 General

Part 2 Reed length

Part 3 Root content

Part 4 Defects

Part 5 Foreign matter

Part 6 Bulk density

Part 7 Bundle strength

Part 8 Fineness

(Continued from page 2)

Members

DR C. R. DEBNATH

SHRI S. R. DEV
SHRI AVADH BIHARI DIXIT
SHRI UMA SHANKAR HALDER
SHRI MADAN LAL KALA
SHRI PURANMULL KANKARIA
SHRI RATICHAND BOTHRA (Alternate)
SHRI RATICHAND BOTHRA (Alternate)
SHRI PRAMODA KISHORE PATTANAIK
SHRI PRAMODA KISHORE PATTANAIK
SHRI CHAKRADHAR PRADHAN
SHRI CHAKRADHAR PRADHAN
DR D. N. RAM
SHRI K. RAMA RAO
DR S. R. RANGANATHAN
GOVERNMENT OF Bihar
GOVERNMENT

SHRI S. PALIT (Alternate)
SHRI BURRA VENKATESWARA RAO
SHRI KULANAND SAHA
SHRI JITENDRA SARKAR
SECRETARY, ASSAM STATE AGRICULTURAL MARKETING BOARD
SHRI A. K., SENGUPTA
SHRI S. L. TAPARIA
SHRI THULESWAR NATH

Representing

Jute Technological Research (ICAR), Calcutta
Government of Tripura
Jute Growers, Uttar Pradesh
Jute Growers, West Bengal
Bengal Jute Dealers' Association, Calcutta
Calcutta Baled Jute Association, Calcutta
ernate)
Government of Uttar Pradesh
Jute Growers, Andhra Pradesh
Government of Orissa
Jute Growers, Bihar
Jute Growers, Orissa
Government of Bihar
Government of Andhra Pradesh
Indian Jute Industries' Research Association,

Jute Growers, Andhra Pradesh Jute Growers, Bihar Jute Growers, Tripura Government of Assam

Government of West Bengal Jute Balers' Association, Calcutta Jute Growers, Assam

Ad-hoc Panel for Grading Bimli Fibre

Calcutta

SHRI J. L. BANTHIYA SHRI G. M BHANDARI SHRI B. B. BHOWMICK

SHRI K. D. KHANDELWAL SHRI A. K. MITRA

SHRI N. K. RAWAT SHRI A. N. SANYAL SHRI S. L. TAPARIA Chitavalsah Jute Mills Co Ltd, Chitavalsah Indian Jute Mills Association, Calcutta
Jute Technological Research Laboratories (ICAR), Calcutta
Indian Jute Mills Association, Calcutta
Indian Jute Industries' Research Association,
Calcutta
Chitavalsah Jute Mills Co Ltd, Chitavalsah
Jute Corporation of India Ltd, Calcutta
Jute Balers' Association, Calcutta

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Pressure, stress

QUANTITY	UNIT	Symbol	
Length	metre	m	
Mass	kilogram	kg	
Time	second	S	
Electric current	ampere	A	
Thermodynamic temperature	kelvin	K	
Luminous intensity	candela	cd	
Amount of substance	mole	mol	
Supplementary Units			
QUANTITY	UNIT	SYMBOL	
Plane angle	radian	rad	
Solid angle	steradian	sr	
Derived Units			
QUANTITY	Unit	Symbol	DEFINITION
Force	newton	N	$1 N = 1 \text{ kg.m/s}^2$
Energy	joule	J	1 J = 1 N.m
Power	watt	W	$1 \mathbf{W} = 1 \mathbf{J/s}$
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	$1 T = 1 \text{ Wb/m}^2$
Frequency	hertz	Hz	1 Hz = 1 c/s (s-1)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A

Pa

 $1 \text{ Pa} = 1 \text{ N/m}^2$

pascal